

# DHL43

## 43" FHD LCD Monitor



### Features:

- Professional thermal design to extend equipment lifespan
- Using tamper-proof metal housing
- Built-in 3D COMB filter and 3D noise reduction
- High fidelity digital processing for a brilliant and vivid video
- Infrared, RS232 double mode, supporting remote PC control
- Support multiple signals, such as HDMI, DVI, VGA, BNC, USB multimedia, Audio, RS232



### Technical Specification

#### Model

Model	DHL43
-------	-------

#### Display

Screen Size	43"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	450 cd/㎡
Contrast	1100:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	12ms
Refresh Rate	60Hz

#### Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, Audio×1, RJ45(RS232)×1, USB×1	
Output	CVBS(BNC)×2, RJ45(RS232)×1	
	Speaker	10W×2

#### General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	45W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	15.5kg (34.2lb)	
Gross Weight	19kg (41.9lb)	
Bezel Width	25.5mm (U/L/R/B)	
Wall Mount	200×200mm (7.9"×7.9")	
Dimension without standard (W×H×D)	994.5×592.7×52.9mm (39.2"×23.4"×2.1")	
Package(W×H×D)	1130×735×205mm (44.5"×28.9"×8.1")	
Work Environment	Temperature	0°C~50°C (32°F~122°F)
	Humidity	20%~90%

#### Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

#### Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

