

DHL49

49" FHD LCD Monitor



Features :

- Professional thermal design to extend equipment lifespan
- Using tamper-proof metal housing
- 8ms fast response time for no motion blur, judder or ghosting
- Built-in 3D COMB filter and 3D noise reduction
- High fidelity digital processing for a brilliant and vivid video
- Infrared, RS232 double mode, supporting remote PC control
- Support multiple signals, such as HDMI, DVI, VGA, BNC, USB multimedia, Audio, RS232



Technical Specification

Model

Model	DHL49
-------	-------

Display

Screen Size	49"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	450 cd/ m ²
Contrast	1100:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz

Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, Audio×1, RJ45(RS232)×1, USB×1	
Output	CVBS(BNC)×2, RJ45(RS232)×1	
Speaker	10W×2	

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	60W	
Consumption (Standby)	≤1W	
Type	Internal	
Net Weight	19.5kg (43.0lb)	
Gross Weight	23.5kg (51.8lb)	
Bezel Width	25.5mm (U/L/R/B)	
Wall Mount	300×300mm (11.8"×11.8")	
Dimension without standard (W×H×D)	1127.1×667.3×52.9mm (44.4"×26.3"×2.1")	
Package(W×H×D)	1275×810×205mm (50.2"×31.9"×8.1")	
Work Environment	Temperature	0 C~50 C (32°F~122°F)
	Humidity	20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

